



DISPENSE GUIDELINES

SCOTTISH BROWN ALE

5.2%




TASTING NOTES

A smooth, rich and nutty 5.2% ale. Lots of biscuity malt character from the best quality Scottish malted barley. Crystal malts add toffee and caramel taste and black malt contributes a crisp, astringent balance. Challenger and Goldings hops add a fresh herbal and resin hop note as well as a refreshing bitter linger to balance with the sweet malt character.

DISPENSE SPECIFICATION

- Gas - 30/70 (CO₂/Nitrogen)
- PSI @ 11°C - 34 - 36 PSI
- Temperature - 6 - 8°C
- Dispense speed - 18 - 22 seconds
- Creamer plate - 5 hole 30 thou creamer plate
- Coupler - sankey
- Keg storage - min. 24hrs before sale @ 11- 13°C



Sankey coupler



Creamer plate

REMEMBER

LINE CLEANING

Clean all lines at least every seven days.

Mon	1	8	15	22	29
Tue	2	9	16	23	30
Wed	3	10	17	24	31
Thur	4	11	18	25	
Fri	5	12	19	26	
Sat	6	13	20	27	
Sun	7	14	21	28	

SPOUTS / CREAMER PLATES

Remove and clean at the end of every day.



SERVE

Use a clean branded glass every time.



SWITCH OFF DISPENSE GAS AT THE END OF EVERY SESSION



LINE CLEANING: HEALTH & SAFETY

ALL LINES

Clean all lines at least every seven days.

Mon	1	8	15	22	29
Tue	2	9	16	23	30
Wed	3	10	17	24	31
Thur	4	11	18	25	
Fri	5	12	19	26	
Sat	6	13	20	27	
Sun	7	14	21	28	

DETERGENT

Always make a fresh detergent mix.



WARN STAFF

Never clean lines when customers are present.



GOGGLES, GLOVES & APRON

Must be worn.



GLASSES


Do not use for measuring beer line cleaner.



LINE CLEANING: KEG BEERS


1. PRODUCT GAS

Turned off.




2. COUPLING HEADS

Connect to cleaning sockets.




3. GAS PUMP

Turned on (if fitted).



4. LINES

Use clean water to remove beer from lines.



5. SPOUTS/SPARKLERS

Remove & clean.




6. LINE CLEANING DETERGENT

Add recommended line cleaning detergent at the correct strength.



7. LINE PRIMER

Pass solution through top of line primer.



8. FILL LINES

Pull solution through to the bar.



9. TIMINGS

Total contact time of 30 mins. Pull through every 10 mins.



10. REMOVE LINE CLEANER

Flush lines out with 10 litres of clean water per tap.




11. SPOUTS/SPARKLERS

Replace spouts & sparklers.




12. COUPLING HEADS

Reconnect couplers to correct product.




13. PRODUCT GAS

Turned back on.



14. LINE PRIMER

Fill with product.



15. FILL LINES

Pull product through to the bar.



16. SAMPLE


C: Clarity
A: Aroma
T: Taste
T: Temperature



CELLAR & EQUIPMENT CONDITION


TEMPERATURE

Check Daily.



VENTILATION

Maintain adequate ventilation to prevent build up of gas and mould growth. Ventilate for 10 minutes daily.




HYGIENE

Keep cellar clean and tidy.



EQUIPMENT

Switched on. Topped up. Dust free.



LINE CLEANING

Clean all lines at least every seven days. See separate 'Line Cleaning Card'.

Mon	1	8	15	22	29
Tue	2	9	16	23	30
Wed	3	10	17	24	31
Thur	4	11	18	25	
Fri	5	12	19	26	
Sat	6	13	20	27	
Sun	7	14	21	28	

PREPARATION


KEG STORAGE

24 - 48 hours before sale. Always at 11 - 13°C.




SECONDARY VALVE

Turn ON at start of session. Turn OFF at end of session.




REMOTE COOLERS

Turned on and working 24 hours a day.



HEAT DUMP


Keep grills clean.



SERVING


CONNECTION

1. Turn gas off
2. Correct product - check
3. Check coupler hygiene
4. Connect
5. Turn on gas
6. Check gas pump (if fitted)
7. Fill up line primer



KEG COUPLER Must be fully engaged

GAS PUMP



LINE PRIMER



CHECK QUALITY

C: Clarity
A: Aroma
T: Taste
T: Temperature



SERVE TO CUSTOMERS Use a clean glass every time